

Platform

2.50 m X 5.35 m Platform (7.55 m extended)
Single hydraulic powered deck extension
Composite treated wooden floor
Fold-down/drop-down handrails
Self-closing gate
Removable platform console box
Platform console function status LED's¹
Lanyard attach points
Proportional drive control
Load sensing system
Two speed drive selection
Hydraulic differential lock

Power & Transmission

Deutz D2011L04i (42kW) diesel engine
Gull wing steel engine / valve compartment hoods
Engine monitoring system with integral shut-down
Hydraulic transmission
Four wheel drive
Drive disconnect/brake release

¹ Indicator LED lights on platform control console for tilt, high drive, lift, drive and overload interlocks.

Functional Equipment & Accessories

Nivolux self-levelling hydraulic jacks
Steel mesh scissor arm guards
315/80 R22.5 foam filled lug tread tyres
Oscillating rear axle
3 degree tilt indicator light with cut-out
Ground control selector switch with key lock
Full grease lubrication on all scissor arm bushings
Scissor maintenance prop
Manual descent system
Hour meter
Horn
Travel alarm
Lifting/tie down lugs

Available Options

AC cable to platform



245-25

A. Platform height - elevated	24.50 m
B. Platform height - lowered	3.14 m
C. Platform railing height	1.10 m
D. Stowed height (rails folded)	3.24 m
E. Platform size	2.50 m x 5.35 m
F. Platform length fully extended	7.80 m
G. Overall width	2.50 m
H. Overall length	5.78 m
I. Wheelbase	3.90 m
Ground clearance	0.26 m
Platform capacity	750 kg
Capacity on deck extension	750 kg
Lift/lower time	125 / 80 sec
Maximum drive height	21.00 m
Deck extension	Hydraulic
Machine weight ¹	16,300 kg
Maximum ground bearing pressure	6.0 kg/cm ²
Drive speed - high	2.3 km/h
Drive speed - elevated	0.5 km/h
Gradeability (4WD)	25%
Turning radius - inside	1.50 m
Turning radius - outside	6.20 m
Axle oscillation	0.15 m (±)
Tyres	315/80 R22.5 Foam Filled
Diesel engine	42 kW Deutz D2011L04i
Fuel tank capacity	90 L
Hydraulic system	325 L

¹ Certain options or country standards may increase weight and/or dimensions.

